


SMM C/P 1989 DOY226 50 +/- 0 degrees

height = h + velocity*time

data points = 2



tstart=DOY226 4:30 +/- 0.0 [min.]
radial velocity= 126. +/- 0. [km/sec]


1989 Day 226

GOES-7 OPTICAL DATA TOGETHER

STOP
Ret..

BEGIN: 14 AUG 89

Watts meter²



GOES 7 0.5-4.0A GOES 7 1.0-8.0A
OPTICAL FLARES

14/0300

14/0350

14/0500

SAA's
NIGHT

GOES-7 1 MIN DATA: OPTICAL FLARE DUR, IMP, REGION

RUH: 1557UT
20 AUG 89

This is a 1 order run

INPUT:

year	day	time	radii	error in radius	error in angle	datatype
1989	226	8:29: 7	3.60	+/- 0.15	50.0 +/- 1.0	SMM
1989	226	10: 1:12	4.60	+/- 0.25	50.0 +/- 1.0	SMM

Structure being measured:

Top of Fuzzy Front

OUTPUT:

START TIME:

Event began at $t = 0 + -0.210E+03 +/- 0.000E+00$ [minutes]

In more convenient units:

Event began at DOY 226 4:30 +/- 0.000E+00 [minutes]

Origin defined at DOY226 8: 0

RADIAL INFORMATION:

RADIAL VELOCITY = 126. +/- 0. km/sec

The computed RADIAL coefficients and errors FROM NLLST2 are:

c(1) = 0.328E+01 +/- 0.279E-06 [solar radii]
c(2) = 0.109E-01 +/- 0.415E-08 [radii/min]
c(2) = 0.126E+03 +/- 0.481E-04 [km/sec]
c(3) = 0.000E+00 +/- 0.000E+00 [radii/min**2]
c(3) = 0.000E+00 +/- 0.000E+00 [km/sec**2]

ANGULAR INFORMATION:

ANGULAR VELOCITY = 0.0000E+00 +/- 0.0000E+00[radians/sec]

The computed ANGULAR coefficients and errors FROM NLLST2 are:

a(1) = 50. +/- 0. [degrees]
a(2) = 0.000E+00 +/- 0.000E+00 [degrees/min]
a(2) = 0.000E+00 +/- 0.000E+00 [rad/sec]
a(3) = 0.000E+00 +/- 0.000E+00 [degrees/min**2]
a(3) = 0.000E+00 +/- 0.000E+00 [rad/sec**2]

THE TANGENTIAL AND TOTAL VELOCITIES AT EACH DATA POINT ARE:

The TANGENTIAL velocity at 8:29 = 0. km/sec

The TOTAL velocity at 8:29 = 126. km/sec

The TANGENTIAL velocity at 10: 1 = 0. km/sec

The TOTAL velocity at 10: 1 = 126. km/sec

The following info is for estimating goodness of the fit

Number data points = number of coefficients. No error analysis is possible.

Correlation coefficient is not computable!